



PG/EPUS/000001
Rec'd PCT/PTO 14 DEC 2004

10/517930



INVESTOR IN PEOPLE

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office
REC'D 21 JUL 2003
Concept House
Cardiff Road
Newport PCT
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

He Behen

Dated

7 May 2003

BEST AVAILABLE COPY



The
Patent
Office

Patents Act 1977
(Rule 16)

17JUN02 E726144-11 002898
P01/7700 0.00-0213781.8

The Patent Office

Cardiff Road
Newport
Gwent NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1.	Your reference	J3671(C)/PMK	
2.	Patent application number (The Patent Office will fill in this part)	0213781.8	14 JUN 2002
3.	Full name, address and postcode of the or of each applicant (underline all surnames)	UNILEVER PLC UNILEVER HOUSE, BLACKFRIARS LONDON, EC4P 4BQ	
	Patents ADP number (if you know it)		
	If the applicant is a corporate body, give the country/state of its incorporation	UNITED KINGDOM	1628 001
4.	Title of the invention	DOMESTIC SPRAYING DEVICE	
5.	Name of your agent (if you have one)	ELLIOTT, Peter William	
	"Address for Service" in the United Kingdom to which all correspondence should be sent (including the postcode)	PATENT DEPARTMENT, UNILEVER PLC COLWORTH HOUSE, SHARNBROOK BEDFORD, MK44 1LQ	
	Patents ADP number (if you know it)	6573927001	
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)
		Date of filing (day / month / year)	
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day/month/year)
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d))		
	YES		

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

9

Claim(s)

2

Abstract

1

Drawing(s)

-

10. If you are also filing any of the following, state how many against each item.

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

1

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature(s)



Date: 14/06/02

Sandra Jane EDWARDS, Authorised Signatory

12. Name and daytime telephone number of person to contact in the United Kingdom

Petra Kimber, Tel 01234 222893

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.

DUPLICATE

- 1 -

DOMESTIC SPRAYING DEVICE

The present invention relates to a hand-held domestic
5 spraying device that utilises a MEMS (micro-electro
mechanical system) pump to force a liquid composition from a
reservoir towards a spray nozzle.

Hand-held domestic spraying devices of the prior art have
10 utilised a variety of means for transferring a liquid
composition from a storage reservoir towards a spray nozzle.
A widely used option has been to use volatile propellants,
such as liquefied hydrocarbons or chlorofluorocarbons, to
pressurise the liquid composition. However, it is
15 increasingly recognised that the addition to the atmosphere
of VOCs/greenhouse gases may have detrimental environmental
consequences.

An alternative means of supplying the necessary force to the
20 liquid composition has been the use of hand-powered
mechanical mechanisms, such as squeeze spray and trigger
spray devices. Unfortunately, such mechanisms suffer the
inherent problem of requiring physical effort on the part of
the consumer. In addition, devices utilising such
25 mechanisms tend not to produce good quality sprays.

The problems of the above approaches have been overcome by
the use of electrically powered pumps. Such pumps may be
used directly on the liquid composition or they may be used
30 as air pumps - the resulting air pressure modification
providing the force required to move the liquid composition.

- 2 -

EP 949,006 A1 (Procter and Gamble) describes the use of an electrically powered pump to directly move a liquid cleaning composition from a reservoir towards a spray nozzle. US 3,522,911 (Collins) and US 4,034,916 (Helene Curtis) describe the use of electrically powered air pumps as compressors, supplying pressurised air that is used to force a liquid composition from a reservoir towards a nozzle. WO 99/49904 (Quest International) describes the use of an electrically powered air pump to create an air stream that draws a liquid composition from a reservoir using a venturi effect.

The problem with electrically powered pumps, as described above, is that they are generally relatively expensive and bulky. In addition, their power consumption can be quite high. As a result, traditional electrically powered pumps are not ideal for use in disposable, hand-held, domestic spray devices. For this reason, devices that utilise such pumps have previously been envisaged as non-disposable devices, requiring re-fill packs of the liquid composition to be dispensed in order to be economically viable.

We now have found that a hand-held domestic spray device utilising an electrically powered pump may be made using a MEMS pump. Such devices have all the benefits of electrically powered pumps described above and the further benefits of being relatively inexpensive and light. In addition, the relatively low cost and size of such devices makes them potentially disposable and not tied to use with re-fill packs. A further advantage is that such devices can

produce a spray with very little noise; this can be a valuable benefit in the domestic environment.

MEMS pumps have previous been described for use in military
5 and laboratory applications. WO 00/28215, US 5,836,750,
US 6,106,245, and US 5,836,750 (all by Honeywell Inc.)
describe such pumps and usage.

Summary of the Invention

10

In a first aspect of the present invention, there is
provided a hand-held domestic spraying device comprising a
reservoir for holding a liquid composition, a nozzle means
for producing a spray from said liquid composition, an
15 electrically powered pump for creating the force required to
move the liquid composition from the reservoir towards the
nozzle, and a control means for activating the electrically
powered pump, characterised in that the electrically powered
pump is a MEMS pump.

20

In a second aspect of the present invention, there is
provided a method of spraying a liquid composition using a
device as described in the first aspect of the invention.

25 In a third aspect of the invention, there is provided a
device as described in the first aspect of the invention and
a liquid composition for spraying therefrom.

Detailed description

The hand-held spraying device of the present invention may be used with numerous liquid compositions and for many domestic applications. It is particularly suitable for application of cosmetic compositions, which are generally applied directly to the human body. Examples of such cosmetic compositions include hair sprays, perfume sprays, deodorant body sprays and underarm products, in particular antiperspirant compositions. The MEMS pump provides a means of rapidly moving the liquid compositions from the reservoir towards the nozzle and thereby enables a good spray quality to be achieved at a high flow rate. A further benefit resulting from the use of an electrically powered MEMS pump is that the spray device is comparatively energy efficient, the MEMS pump having a relatively low power consumption. The above benefits are independently and collectively advantageous for liquid cosmetic compositions that have to be applied to the human body, where it is desirably to be able to apply the composition quickly in the form of a good quality spray and also to have a device that does not quickly run out of power.

Any type of MEMS pump may be used in the spray device of the invention. The pumps are characterised by comprising micro-channels having sub-millimeter diameters and operating using electrostatic pressure generation. Typical micro-channel diameters are from 1 to 500 μm , in particular from 10 to 300 μm . The pumps are typically fabricated using processes compatible with those used in semiconductor technology.

silicones and plastics, with the proviso that the material must be capable of being electrically charged. The pumps may operate by positive displacement, the different principles being piston, gear, lobe, mohno, diaphragm, centrifugal, and hose. The use of diaphragm pumps, where liquid displacement is achieved by the deformation of an elastic membrane, is a preferred option. Micro-peristaltic pumps are another option.

10 Particularly preferred MEMS pumps for use in the present invention have a plurality of elementary cells, each of said cells comprising:

a body forming an electrode cavity having at least one electrode having a curved surface facing toward a curved surface on a facing part of said body to define said cavity, said body including electrical activation means for selectively energising said electrode;

15 a diaphragm mounted and grounded in said body under tension and having a major portion located in said cavity between said curved surfaces, said diaphragm being adapted to deflect toward and away from said electrode curved surface; lateral conduit means in said body forming an end conduit, said lateral conduit means being operably connected to the portion of said diaphragm mounted in said body and positioned to be opened and closed by movement of said diaphragm for controlling flow of fluid through said end conduit;

25 vertical conduit means operatively connected to at least one curved surface of said cavity for controlling flow of fluid there through by movement of said diaphragm into and out of contact with said vertical conduit means; and

30

interconnecting conduit means for connecting said cell to said plurality of cells to form said MEMS pump; whereby activation of said electrode causes movement of said diaphragm toward said curved surface of said electrode and
5 deactivation of said electrode allows said diaphragm to return to its original position, to thereby move fluid into and out of said body.

In order to achieve a good transfer rate for the liquid
10 composition, it is highly preferred to use an array of MEMS pumps arranged in parallel, optionally with output micro-channels combining together to give a single channel.

The MEMS pump may be used to act directly upon the liquid
15 composition, forcing it towards the nozzle means. In such embodiments, the MEMS pump acts as a liquid pump and is situated either within or adjacent to the reservoir holding the liquid composition or is connected thereto by a conduit which provides for transfer of the liquid composition from
20 the reservoir to the MEMS pump.

In alternative embodiments, the MEMS pump acts as an air pump and results in an air pressure modification adjacent to the liquid composition and thereby provides the force
25 required to move the liquid composition towards the nozzle means.

In certain embodiments in which the MEMS pump acts as an air pump, its function is to act as an air compressor,
30 increasing the air pressure adjacent to the liquid

forces it towards the nozzle means, often via a transfer conduit.

5 In other embodiments in which the MEMS pump acts as an air pump, it acts to create an air stream that serves to draw the liquid composition from the reservoir using a venturi effect. In such embodiments, the air flow creates a reduced pressure environment adjacent to the liquid composition, typically at the outer end of a transfer conduit contiguous
10 with the reservoir for the liquid composition. The reduced pressure draws the liquid composition from the reservoir and into the air stream. In embodiments comprising a transfer conduit leading from the reservoir, the end of the transfer conduit may be considered to be part of the nozzle means
15 (*vide infra*).

The nozzle means is responsible for creating and often directing the spray produced from the liquid composition. The nozzle means may be any of those typically used in the
20 art, ranging from simple exit orifices to more complicated venturi atomisation nozzles. Preferred nozzles comprise a means of increasing droplet break-up beyond that achieved by the passage of the liquid composition through a simple exit orifice. Swirl chambers of the type known in the art are
25 suitable for use in this manner.

The control means for activating the electrically powered pump may be of any appropriate form. Typical examples include push buttons, toggle switches, or slide-operated
30 switches. The activation will typically involve supply of electrical power to the pump.

The source of the electrical power is preferably comprised within the device itself, although an external power supply may be used. The device may comprise a capacitor, battery or photo-voltaic cell as a source of electrical power.

5

In many embodiments there exists a transfer conduit for transfer of the liquid composition from the reservoir towards the nozzle means. The transfer conduit may have various positions relative to the MEMS pump. When the MEMS pump acts direct upon the liquid composition, the transfer conduit may be located between the reservoir and the pump, between the pump and the nozzle means, or there may be a transfer conduit in both of these locations. When the MEMS pump acts as an air compressor, the transfer conduit runs from the reservoir to the nozzle means, the MEMS pump being separately located.

When present, the transfer conduit preferably comprises one or more valves. Such valves may function to prevent leakage of the liquid composition from the reservoir when the pump is not operating. Positive pressure on the reservoir side of the valve or negative pressure on the nozzle side of the valve may cause the opening of such valves.

25 The hand-held spraying devices of the present invention are able to achieve high fluid output, for example from 30 ml/hr. to 500 ml/hr., and, in particular, from 45 ml/hr. to 180 ml/hr., whilst still maintaining good spray quality. Spray quality may be defined by the fineness of the droplets achieved and/or by the narrowness of the particle size

desirable to achieve a volume mean particle size of from 1 μm to 100 μm , in particular from 5 μm to 50 μm , and especially from 5 μm to 25 μm .

5 Liquid compositions used with the device of the present invention frequently comprise a liquid carrier fluid comprising a C2 to C4 alcohol, for example ethanol, propylene glycol, propanol, or iso-propanol. When such
10 application to the human body, the good spray quality attained leads to an excellent sensory benefit for the user. Suitable liquid compositions typically comprise C2 to C4 alcohol at a level of from 5% to 95%, in particular from 25% to 80%, and especially from 40% to 75% by weight of the
15 composition. Liquid compositions comprising ethanol are particularly suitable for use with the device of the present invention.

The aforementioned liquid carrier fluid may also comprise
20 water in an amount from 0.1% to 50% by weight of the composition.

CLAIMS

1. A hand-held domestic spraying device comprising a
reservoir for holding a liquid composition, a nozzle
5 means for producing a spray from said liquid
composition, an electrically powered pump for creating
the force required to move the liquid composition from
the reservoir towards the nozzle, and a control means
for activating the electrically powered pump,
10 characterised in that the electrically powered pump is
a MEMS pump.
2. A device according to claim 1, wherein the MEMS pump
acts directly upon the liquid composition, forcing it
15 towards the nozzle means.
3. A device according to claim 1, wherein the MEMS pump
acts as an air pump resulting in an air pressure
modification adjacent to the liquid composition and
20 providing the force required to move the liquid
composition from the reservoir towards the nozzle
means.
4. A device according to claim 3, wherein the MEMS pump
acts as air compressor, increasing the air pressure
25 adjacent to the liquid composition.
5. A device according to claim 3, wherein the MEMS pump
acts to create an air stream that serves to draw the
30 liquid composition from the reservoir using a venturi

6. A device according to any of the preceding claims, comprising a transfer conduit for transfer of the liquid composition from the reservoir towards the nozzle means.

5

7. A device according to claim 6, wherein the transfer conduit comprises one or more valves.

ABSTRACT

A hand-held domestic spraying device comprising a reservoir for holding a liquid composition, a nozzle means for
5 producing a spray from said liquid composition, an electrically powered pump for creating the force required to move the liquid composition from the reservoir towards the nozzle, and a control means for activating the electrically powered pump, characterised in that the electrically powered
10 pump is a MEMS pump that gives the benefits of energy efficiency, low cost, and potential disposability.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.